# EN

# **Dolphin WAVE 100 Robotic Pool Cleaner** Operating Instructions

# Contents

| 1. INTRODUCTION                              | 2   |
|--|-----|
| 2. SPECIFICATIONS                            | 2   |
| 3. WARNINGS AND CAUTIONS                     | 2   |
| 3.1. Warnings                                | 2   |
| 3.2. Cautions                                | 2   |
| 4. POOL CLEANER PARTS                        | 3   |
| 5. USING THE POOL CLEANER                    | 4   |
| 5.1. Set up                                  | 4   |
| 5.2. Putting the Pool Cleaner into the pool  | 5   |
| 5.3. Removing the Pool Cleaner from the pool | 5   |
| 5.4. Maintenance                             | 6   |
| 5.5. Off-season storage                      | 7   |
| 6. POWER SUPPLY                              | 8   |
| 7. REMOTE CONTROL UNIT                       | 9   |
| CADDY ACCEMBLY                               | / 1 |

# **Dolphin WAVE 100 Pool Cleaner**

# Operating Instructions

# 1. INTRODUCTION

Thank you for purchasing a Maytronics Robotic Pool Cleaner.

We are sure that your Maytronics Robotic Pool Cleaner will provide you with reliable, convenient and cost effective pool cleaning. Its reliable filtration in all pool conditions and all-surface climbing brush enhance maximum pool hygiene.

The Robotic Pool Cleaners by Maytronics deliver advanced cleaning technology, long lasting performance and easy maintenance.

# 2. SPECIFICATIONS

Motor protection: IP 68

Minimum depth: 0.80m / 2.6ft Maximum depth: 5m / 16.4ft

# 3. WARNINGS AND CAUTIONS

# 3.1. Warnings



- Use the originally supplied power supply only
- Ensure the electrical outlet is protected by a ground fault interrupter (GFI) or an earth leakage interrupter (ELI)
- Keep the power supply out of standing water
- Position the power supply at least 3m / 10ft away from the edge of the pool
- Do not enter the pool while the pool cleaner is working
- Unplug the power supply before servicing


#### 3.2. Cautions

When not in use store the Pool Cleaner on the Caddy in a shaded area.

Use the Pool Cleaner in the following water conditions only:

| Chlorine    | Max 4 ppm          |  |  |
|-------------|--------------------|--|--|
| рН          | 7.0 - 7.8          |  |  |
| Temperature | 6-34°C / 43-93°F   |  |  |
| NaCl        | Maximum = 5000 ppm |  |  |

# 4. POOL CLEANER PARTS




29/12/2013 9:59 AM

# 5. USING THE POOL CLEANER

# 5.1. Set Up

Before using the Pool Cleaner for the first time perform the following steps.

Unwind the cable and stretch it out completely so that it has no kinks.




GFI/ELI

3m/10ft

Remove the plastic coverings before use.

POWER SUPPLY

Attach the floating cable to the power supply by inserting it with the notch on the connector (1) lined up with the groove in the socket on the power supply and turning clockwise (2).



Change diagonal handle position for water line sideway movement. To adjust the handle angle:

- **A.** Press the latch down and hold it in position.
- **B.** Move the handle to the desired position and release the latch to hold the handle in place.

#### 1,2: Normal advance

More efficient cleaning action on water-line.

#### 3,4: Fast advance


Fast speed – for faster but less efficient cleaning action on water-line.

**Dolphin WAVE 100 Pool Cleaner** | Operating Instructions


# 5.2. Putting the Pool Cleaner into the pool

If the foam climbing rings on the brushes are dry soak them in water until soft.

Shake the robot from side to side or turn it upside down to release trapped air. Let it sink to the pool floor.



Turn the power supply ON.





# 5.3. Removing the Pool Cleaner from the pool


The robot will perform automatic shut-off at the end of the cleaning cycle.



Turn OFF and unplug the power supply.








Using the floating cable, bring the Pool Cleaner to the pool's edge.





DO NOT PULL THE POOL CLEANER FROM THE POOL USING THE CABLE.


# 5.4. Maintenance


Clean the filter bag with a hose. Periodically clean the brushes with a hose. It is recommended to periodically wash the filter bag in a washing machine. Use gentle cycle program.



















# Cleaning the impeller

Unplug the power supply.


If you notice debris trapped in the impeller, open the impeller and remove the debris.





# Cable


To remove the kinks, stretch the cable out completely and let it sit for at least a day in the sun.



# 5.5. Off-season storage

If the pool cleaner will not be in use for an extended period, perform the following storage steps:

- Make sure that no water is left in the pool cleaner
- Thoroughly clean the filter bag and insert in place
- Roll up the cable so that it has no kinks and place on the Caddy
- Store the pool cleaner upright on the Caddy in a protected area out of direct sun/rain/frost at a temperature of between 5°-45°C / 41°-113°F




**Dolphin WAVE 100 Pool Cleaner** | Operating Instructions

# 6. POWER SUPPLY

Digital "Switch-Mode" Power Supply with full filter bag and delay indicator.

- Input 100-250 AC Volts
- 50-60 Hertz
- 180 Watt
- Output <30 VDC
- IP 54







# Full filter bag indicator and Reset button

The power supply is equipped with a filter bag status indicator.

The red LED indicates two filter conditions.

- When blinking The filter is partially blocked.
- When lighted The filter is blocked and must be emptied and cleaned.

If the LED does not turn off after the filter bag had been emptied and cleaned, press the RESET button while the robot is working.



# **Delay indicator**

The power supply is equipped with a Delay indicator that indicates if the Delay option is activated (through the remote control unit).

# 7. REMOTE CONTROL UNIT


# The Control Panel


The remote control unit (RCU) offers two operation modes – Automatic mode and manual direction control mode.

In automatic mode, the cleaning parameters can be changed.

In manual direction mode, the robot's motion can be controlled manually.

Manual Direction Control Mode





**Dolphin WAVE 100 Pool Cleaner** | Operating Instructions

Press the Manual/Automatic select button and then choose the desired parameters according to the following table:

| Cleaning cycle indicator This determines the length of the cleaning cycle.   | Fast<br>4-hour cycle                                | Efficient 6-hour cycle for everyday use. (Default setting)         | Extra<br>8-hour cycle  |  |
|--|---|--|--|--|
| Delay time indicator This determines when the pool cleaner starts to work. Delaying allows the dirt to settle to the bottom of the pool. | Immediate start<br>(Default setting)                | One-hour delay   | Two-hour delay   |  |
| Cleaning action indicator Allowing you to choose from the following options.   | Standard Floor and wall cleaning. (Default setting) | Ultra-clean Stronger suction and slower movement. (floor and wall) | Floor only Cleans only the floor and the area where the floor and walls meet | Walls only Cleans walls and waterline only |

#### Note:

- After 2 minute if no button is pressed, the Remote Control Unit will shut-down and the Pool cleaner will continue to work in the previous settings.
- When the "Ultra-Clean" and "Walls Only" options finish their cycles, the Pool Cleaner will return to default settings.